

Remove smoke and air

HAUTAU SBS

Well, it works! Aesthetic and well-proven functionality, and easy mounting has been solved by the versatile HAUTAU electrical stay fitting SBS.



Optimal pressure points:
For tilt windows with stays uppermost the symmetrical left and right inserts provide a perfect closing position - and at the same time appears harmonious. For side mounting the lower the the stay sits the greater the window opening is. Pay careful attention here to the proportions and maximum weight. The opening angle of the rotating sash. Is about 78°.

Less space required!
The electrical stay fitting SBS is also suitable for narrow windows profiles. Large openings!
The stays achieve a positioning distance of from 350 to 600 mm (rotating sashes over 600 mm).

Intensive room airing!
Large extraction areas guarantee quick, energy-saving fresh air.



HAUTAU

The advantages

24 V direct motor drive

The HAUTAU electrical stay fitting SBS is suitable for tilt, clap and rotating sashes or for swing and vertical sashes (façade sashes and roof surface windows) made of timber, plastic and light alloy. Here the technically proven combination of stay fitting and electric motor from the RWA centre or from the air control takes over. The space required is agreeably small: the stay fitting with individual adjustment - depending on type of mounting - 40 to 55 mm on the frame.

Sophisticated construction

The HAUTAU electrical stay fitting SBS is universally useable - on the top, on the side, in pairs and separately. Optimally chosen pressure points guarantee a perfect closing position with excellent closing and opening pressures - especially with use of two HAUTAU electric stay fittings SBS left and right.

Especially easy mounting

The HAUTAU electrical stay fitting SBS consists of only three parts, for the clap sash outwards there is one more. A terminal block in the motor drive eases the connection of cables, the fastening on the frame made by a bracket. The second rotating axis for tilt sashes at the top is screwed directly onto the base bracket. For mounting uppermost the stay is useable left and right. Rebate inaccuracies are compensated for by the adjustment arrangement in the end cap, the closing pressure can be adjusted optimally for the application.

Infinitely variable control

Thanks to the switch with Stop function the window can take up any open position. Operation is pleasantly quiet. Tandem switch-off takes care of synchronisation, the tracking control regulates the closing sequence of the sash. For window cleaning the sashes are simply released with the security knob on the stay arm.

Would you like detailed information about the electrical stay fitting SBS or other HAUTAU products? Just ask us and we will convince you!



W. HAUTAU GmbH
PO Box 1151
D 31689 Helpsen
Tel +49 57 24 / 393-0
Fax +49 57 24 / 393-138
Info@HAUTAU.de
www.HAUTAU.de

You'll notice if it's HAUTAU.



HAUTAU